


Handheld Scanner

LF1650S


Wmaxvision 威码视



Fast Decode



Screen Scan



Quick Scan



1D Decode



2D Decode



USB

Feature

- Support screen payment function.
- Support Alipay invoicing function.
- NTFast decoding algorithm accurately decode all kinds of barcodes at high speed.
- High level of integration and easy integration into all kinds of equipment and applications.

Application



Suzhou Wmaxvision Technology Co., Ltd.

TEL:0512-86860596

E-MAIL:sales@wmaxvision.com

WEB:http://www.wmaxvision.com

ADD:Building 2, Lianchuang Industrial Park, Dongfu Road, Suzhou Industrial Park, China (Jiangsu)

LF1650S

SPECIFICATIONS

Wmaxvision 威码视

Physical Characteristics

Dimensions: 160mm x 64mm x 97mm

Voltage: 5V

Weight: 140.5g

Starting Current: 160mA

Stand-by Current: 120mA

Work Current: 330mA

Performance Characteristics

Image (Pixels) : 640 pixels (H) x 480 pixels (V)

Light Source: (Aimer) Red color LED; (Illumination) White color LED

Field of View: 48°(Horizontal), 36°(Vertical)

Roll / Pitch / Yaw: 360°, ±65°, ±65°

Print Contrast: 20% minimum reflective difference

Interfaces Supported: USB

Motion Tolerances: 40cm/s

Minimum Resolution: ≥4mil

Symbology Decode Capability

1-D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA、Matrix 2 of 5、Code 11、Code 128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.

2-D: Codeblock A、Codeblock F、PDF417、Micro PDF417、GS1 Composite Codes、QR Code、Data Matrix、MaxiCode、Aztec、HANXIN.

Decode Ranges

Code39(5mil): 30mm-80mm

Code39(13mil): 30mm-180mm

Suzhou Wmaxvision Technology Co., Ltd.

TEL: 0512-86860596

E-MAIL: sales@wmaxvision.com

WEB: <http://www.wmaxvision.com>

ADD: Building 2, Lianchuang Industrial Park, Dongfu Road, Suzhou Industrial Park, China (Jiangsu)

LF1650S

SPECIFICATIONS

Wmaxvision 威码视

User Environment

Operating Temperature : -20°C to 60°C

Storage Temperature : -30°C to 70°C



Humidity : 5% to 95% relative humidity, non-condensing

Shock Specifications : Designed to withstand 1.2m(5') drops

Ambient Light Immunity : 0-100,000 Lux.

Performance may be impacted by bar code quality and environmental conditions

Dimension (unit:mm)



Suzhou Wmaxvision Technology Co., Ltd.

TEL:0512-86860596

E-MAIL:sales@wmaxvision.com

WEB:http://www.wmaxvision.com

ADD:Building 2, Lianchuang Industrial Park, Dongfu Road, Suzhou Industrial Park, China (Jiangsu)